What is claimed is:

A method of forming a honeycomb sandwich composite panel of comprising the steps of:

stacking a dry fabric on both sides of a honeycomb core with a thermosetting sealing material having an adhesive property placed in between;

heating said sealing material and said dry fabric at the curing temperature of said sealing material to cause initial hardening of said sealing material and to dry said dry fabric;

impregnating said dry fabric with a thermosetting resin; and

hardening the resin impregnated into said dry fabric by hot-pressing an entire assembly thus prepared under specific conditions.

2. A method of forming a honeycomb sandwich composite panel comprising the steps of:

stacking a dry fabric on both sides of a honeycomb core with a thermosetting sealing material having an adhesive property placed in between;

hardening said sealing material by heating said sealing material and said dry fabric to the curing temperature of said sealing material and maintaining this temperature for a specified period of time;

impregnating said dry fabric with a thermosetting resin while varying the temperature of said sealing material and said

SUR

dry fabric to a resin impregnating temperature and maintaining this temperature for a specified period of time; and

hardening the resin impregnated into said dry fabric by heating said sealing material and said dry fabric to the curing temperature of said thermosetting resin and hot-pressing them for a specified period of time.

- 3. The method of forming the honeycomb sandwich composite panel as defined in claim 1 or 2, wherein said sealing material is a laminated film formed by laminating a plurality of thermosetting resin films in which glass microbaloons are mixed.
- 4. The method of forming the honeycomb sandwich composite panel as defined in claim 1 or 2, wherein said sealing material is a laminated film formed of at least two thermosetting adhesive films and a carrier material placed between the thermosetting adhesive films.
- 5. The method of forming the honeycomb sandwich composite panel as defined in claim 1 or 2, wherein said sealing material is a laminated film formed of at least two thermosetting adhesive films and a thermosetting resin film placed between the thermosetting adhesive films, with glass microbaloons mixed in the thermosetting resin film.
  - 6. The method of forming the honeycomb sandwich composite panel as defined in claim 1 or 2, wherein said sealing material

The state of the s

is a laminated film formed by laminating a plurality of thermosetting adhesive films.

7. The method of forming the honeycomb sandwich composite panel as defined in one of claims 1 to 6, wherein said sealing material is hardened at a temperature lower than the curing temperature of the impregnating resin.

8. The method of forming the honeycomb sandwich composite panel as defined in one of claims 1 to 6, wherein said sealing material is hardened at a temperature equal to or higher than the curing temperature of the impregnating resin.

9. The method of forming the honeycomb sandwich composite panel as defined in one of claims 1 to 6, wherein said sealing material is hardened at a temperature equal to or higher than the curing temperature of the impregnating resin.

uau 627